



32 CANTILEVERGATE
TRACKSLIDERGATE

33 FACTORIES, ADMINISTRATION CENTRES, PUBLIC BUILDINGS,
SPORTS GROUNDS, AIRPORTS & MILITARY SITES



Standard sizes											
Gate height (m)	1.0	1.2	1.8	2.0	2.1	2.4	3.0				
Single Leaf widths (m)	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0
Double Leaf widths (m)	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0
	Tops				Forged						
Infill	Flush	Serrated	Square	Mitred	Head	TPT	R&N	Single Pointed			
25 x 2 CHS	●	●	●	●	●						
25 x 25 x 2 RHS	●	●	●	●	●						
W' PALE			●				●	●			
D' PALE			●				●	●			
MESH	●	●									

The Sliding Gate Range can be cantilever or track slider with infills to suit requirements.

A range of high quality access controlled gates suitable for sites that require operational safety and security. This range integrates seamlessly with the complete range of Gramm Barrier Systems perimeter security systems and harmonises with all styles of existing or new boundary installations, with an

extensive choice of widths and heights and an almost endless array of infills. Gramm Barrier Systems can customise the Sliding Gate range to suit every application, and tailor each product to satisfy individual requirements.

Manual Sliding Gate
The gate is opened and closed by hand, and locked using a euro cylinder type Locinox lock and key.

