



Designed to be a strong and durable construction, Gramms Palisade fencing provides excellent protection against climbing and cut-through. Palisade fencing with either a 'D' or a 'W' profile to varying specifications including Gas, Water & Electric Companies and Public Sector specifications.



PALISADE

GRAMM PALISADE RANGE

AVAILABLE FROM STOCK SEE PAGE 6

Standard sizes						
Panels						
Fence heights m	Post Centres mm	Pale thickness mm	Pales per bay mm	Rails Cross rails mm	Posts Overall length mm	Post Section mm
1.2	2.75	2	17	45 x 45 x 6	1700	100 x 55
1.5	2.75	2	17	45 x 45 x 6	2000	100 x 55
1.8	2.75	2/2.5	17	45 x 45 x 6	2300	100 x 55
2	2.75	2/2.5/3	17	50 x 50 x 6	2700	100 x 55
2.1	2.75	2/2.5/3	17	50 x 50 x 6	2700	100 x 55
2.4	2.75	2/2.5/3/3.5	17	50 x 50 x 6	3100	100 x 55
3	2.75	2/2.5/3/3.5/3.9	17	65 x 50 x 6	3900	100 x 55 or 127 x 76

Heights
1.2m, 1.5m, 1.8m, 2m, 2.1m, 2.4m
3m and 3.6m heights are available.

Paling tops
Can be single pointed, triple pointed,
square tops, round and notched tops
or rounded only.

Horizontals
Available in 3 standard sizes according
to height and site requirements:
45x45, 50x50 and 65x50mm.

Posts
Available with welded fishplates or
slotted, complete with loose fishplates
that can be concreted-in, base plated
for bolting down or cranked. Posts can
be vertically extended to take barbed
or razor wire.

Panels
Panels can be easily raked to allow for
most site conditions, and can also be
welded at our factory for added
security.

Fixings
All fixings are anti-vandal.

Gates
Standard gates are available or
tailored-made to suit your requirements
including: Locinox locks, **HYDRACLOSE**
self-closers, razor wire extensions
and other bespoke items to suit your
needs. All gates are supplied with rear
hung adjustable hinges, pad-lockable
drop-bolts, multi-holed to suit site
conditions complete with anti-climb
protection.

- Paling thickness**
- 'W' profile 2.0mm - commercial specification.
 - 'W' profile 2.5mm - general purpose to BS: EN: 1722 Pt 12.
 - 'W' profile 3.0mm - security purpose to BS: EN: 1722 Pt 12.
 - 'D' profile 3.0mm - general purpose to BS: EN: 1722 Pt 12.
 - 'D' profile 3.5mm - security purpose to BS: EN: 1722 pt 12.
 - 'D' profile 3.9mm - security purpose to BS: EN: 1722 pt 12.

All our palisade gates are to BS: EN: 1722 pt 12. See our gate range for further details.

Additional security toppings
Gramm Barrier Systems supply additional toppings for security fences including razor wire coils, razor wire tape, barbed wire, rotating spikes. We can also prepare fence posts to take electric security fence on the back and work closely with the major electric security fence manufacturers.

