



PLAYSAFE-BT

**GRAMM RAILING SYSTEMS
PLAYGROUNDS, SCHOOLS, PUBLIC AREAS**

PLAYSAFE meets the requirements of BS: EN: 1176 playground equipment, with gaps not exceeding 89mm and free from any neck entrapments, and is available in a range of over 180 colours.

Gramm PLAYSAFE-BT complements a stimulating environment and has been designed with safety in mind.

AVAILABLE FROM STOCK SEE PAGE 6

Standard sizes						
Fence height (m)	Embedded length of post	Diameter of vertical round (mm)	Spacing of verticals (centres)	Size of horizontals mm	Size of RSJ post	Size of RHS post
1	450	12	95	30 x 10	100 x 55	50 x 50
1.2	500	12	95	30 x 10	100 x 55	50 x 50
1.2	500	16	102	40 x 10	100 x 55	50 x 50
1.5	550	16	102	40 x 10	100 x 55	50 x 50
1.8	600	20	102	50 x 10	100 x 55	70 x 70
2.4	600	22	102	50 x 10	100 x 55	80 x 80

Heights

Produced from solid bar in all heights up to 2.4m.

Horizontals

Available in flat or channel section.

Posts

Intermediates, Corners and Ends are available in a wide range of sizes and materials including: RHS and RSJ, with the provision to be stepped or cranked to suit site conditions, secured

in concrete (supplied complete with optional two support legs per standard panel for concrete-in fixing) or base plated for surface mounting. All posts come with welded steel caps. A range of post head details available for all railings as an optional extra.

Panels

Panels are available as standard to 2.72m wide panels welded in accordance with BS: EN: 1722 Pt9. Panels can also be made to suit your specific requirements - straight or curved.

Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions and robust pad-lockable slide latches.

HYDRACLOSE gates are particularly suited for use with PLAYSAFE-BT.

See our gate range for further details.

