




PROGUARD

**GRAMM MESH SYSTEMS
SCHOOLS, PLAY AREAS, COMMERCIAL BUSINESS, RETAIL OUTLETS**

21



A rigid type system providing excellent visual appearance. Its aesthetic look is especially popular with Architects and Specifiers. Manufactured to BS: EN: 1722 Part 14 – Cat 1 & 2.

Panels

Manufactured using 4mm vertical and 5mm horizontal wires welded at each intersection, complete with pressed beams creating a strong and durable panel. The mesh aperture consists of a 150 x 50/25mm mesh spacing providing excellent see through visibility.

Standard sizes

Heights above the standard range can be achieved using a multi-lift system.

Panels Fence height mtrs	Panel size H x W	Wire diameter V x H mm	Number of beams	Post centres mm	Post section RHS
1.8	1733 x 3005	5mm	3	2820	60*60
2.4	2433 x 3005	5mm	4	2820	60*60

Post system

Standard posts are manufactured from 60 x 60 x 2.5mm Rolled Hollow Section. All posts include threaded inserts, leaving a clean and flush design to the rear face. Specially designed **PROFIX** Securing system brackets are used for quick and easy installation. As an optional extra, a slotted 40 x 5mm flat clamp bar can be used for additional security.

Applications

The **PROGUARD** system is suitable for most applications where general site demarcation is required. Typical examples: schools, public areas, commercial businesses and retail outlets.

Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with rear hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions complete with anti-climb protection. See our gate range for further details.

Additional security toppings

Gramm Barrier Systems supply additional toppings for security fences including razor wire coils, razor wire tape, barbed wire, rotating spikes.

We can also prepare fence posts to take electric security fence on the back and work closely with the major electric security fence manufacturers.

Posts are complete with our unique pro-fix hanging bracket which makes **PROGUARD** very easy and quick to install. Many of our customers say their erectors prefer our system as they can install more metres per day and earn more money.

