




STYLEGUARD-DTV

GRAMM RAILING SYSTEMS
SCHOOLS, PLAY AREAS, COMMERCIAL BUSINESS, RETAIL OUTLETS



Standard sizes

Heights above 2.4m are available on request.

Fence height (m)	Embedded length of post	RHS verts	Spacing of verticals (centres)	Rails	Size of RSJ post	Size of RHS post
1	450	25*25	125	Channel or Flat	100 x 55	50 x 50
1.2	550	25*25	125	Channel or Flat	100 x 55	50 x 50
1.5	550	25*25	125	Channel or Flat	100 x 55	50 x 50
1.8	600	25*25	125	Channel or Flat	100 x 55	70 x 70
2.4	600	25*25	125	Channel or Flat	100 x 55	80 x 80

Diamond-to-View square is a strong tubular railing system manufactured in accordance with BS: EN: 1722 part 9. Supplied with a mitred, flat top or complemented with a range of forged-head finials.

Heights
Verticals can be in any height up to 3.0m and produced from square hollow section, square-to-view or diamond-to-view with either blunt or mitred tops.

Horizontals
Available in flat, rolled steel channel section.

Posts
Intermediates, Corners and Ends are available in a wide range of sizes and materials including: RHS and RSJ, with the provision to be stepped or

cranked to suit site conditions, secured in concrete (supplied complete with two support legs per standard panel for concrete-in fixing) or base plated for surface mounting. All RHS and RSJ posts are manufactured with welded steel caps and a range of post head details are available for all railings as an optional extra.

Panels
Panels are available as standard to 2.72m wide panels welded in accordance with BS: EN: 1722 Pt9. Panels can also be made to suit your

specific requirements - straight, curved or raked.

Gates
Standard gates are available or tailored-made to suit your requirements. All gates are supplied with side hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions and robust pad-lockable slide latches. See our gate range for further details.